



# Lifting Productivity.

### **Ingersoll Rand ELK Series Electric Chain Hoist**

Introducing the new ELK Series hoists that brings you durability, modularity, flexibility packed in an extremely lightweight, modern design. Built to meet an H4 duty cycle classification, the ELK hoist is designed for tough, industrial grade applications. The ELK joins Ingersoll's Rand CLK, MLK and HLK premium, class leading hoist family.



#### **IP65 Protection**

- Water resistant
- Dust tight
- Perfect for outdoor environments
- · Ideal for rental customers



#### **New Custom Profile Chain**

- Case hardened, magnesium phosphate coated
- · Corrosion resistance
- · Less wear, extended life



#### **Closed Gearbox**

- 3-Stage gearing for quiet operation
- Permanent, self-contained lubrication
- Modular design reduces overall maintenance



#### **Custom Configurations\***

- ATEX Certified option
- Food grade option
- Variable frequency drive option
- Wind turbine configuration
- Other options available

#### **Features**

**H4 DUTY CYCLE RATING** (minimum 2m FEM/M5 ISO) designed for both industrial and manufacturing applications.

**BUILT-IN MOTOR** with cooling fins and fan wheel for reduction in operating temperature and disassembly time.

ERGONOMIC, IMPACT RESISTANT PENDANT control for comfortable, durable operation.



## **MODULAR DESIGN** with interchangeable gear box for reduced

maintenance time, parts and complexity



**LIGHTWEIGHT, COMPACT PROFILE** allows for faster, safer installation and disassembly; ideal for mobile applications.



<sup>\*</sup> For custom configurations, please contact your account manager

# We work where you work.

The ELK series hoist has a variety of features to meet the needs of jobs in areas where you need it most. From manufacturing to wind power to construction, the ELK hoist gets the job done.



**Manufacturing** H4 duty cycle for high volume



Wind Power
Custom wind tower
configurations available



**Construction**Custom lengths for a variety of applications





Foundry
IP65 protects from
dust and other
containments



**Rental**Modular, simple design makes for easy maintenance

#### **Specs**

| Capactiy                     |            |                   | Speed  |         | <b>Duty Rating</b> |       | Headroom |     | Body Weight <sup>†</sup> |     | Chain Weight |      |
|------------------------------|------------|-------------------|--------|---------|--------------------|-------|----------|-----|--------------------------|-----|--------------|------|
| Metric                       | lbs        | Base Model        | ft/min | m/min   | HMI (FEM)          | Falls | in       | mm  | lbs                      | kg  | lb/ft        | kg/m |
| Single Pha                   | ase 115/23 | 30V               |        |         |                    |       |          |     |                          |     |              |      |
| 1/4t                         | 550        | ELK25-1NS25 1 ph  | 16     | 5       | H4 (2m)            | 1     | 15"      | 381 | 37.5                     | 17  | 0.23         | 0.34 |
| 1/4t                         | 550        | ELK50-1NS25 1 ph  | 32     | 9.6     | H4 (2m)            | 1     | 19.2"    | 488 | 57.3                     | 26  | 0.46         | 0.69 |
| 1/2t                         | 1100       | ELK50-1NS50 1 ph  | 16     | 5       | H4 (2m)            | 1     | 19.2"    | 488 | 57.3                     | 26  | 0.46         | 0.69 |
| 1t                           | 2200       | ELK50-2NS100 1 ph | 8      | 2.5     | H4 (2m)            | 2     | 20.8"    | 528 | 61.7                     | 28  | 0.46         | 0.69 |
| Three Phase 230/460/575/380V |            |                   |        |         |                    |       |          |     |                          |     |              |      |
| 1/8t                         | 275        | ELK25-1ND12       | 32/8   | 9.6/2.5 | H4 (2m)            | 1     | 15"      | 381 | 37.5                     | 17  | 0.23         | 0.34 |
| 1/4t                         | 550        | ELK25-1ND25       | 32/8   | 9.6/2.5 | H4 (2m)            | 1     | 15"      | 381 | 37.5                     | 17  | 0.23         | 0.34 |
| 1/4t                         | 550        | ELK50-1HD25       | 63/16  | 19.5/5  | H4 (2m)            | 1     | 19.2"    | 488 | 57.3                     | 26  | 0.46         | 0.69 |
| 1/2t                         | 1100       | ELK50-1ND50       | 32/8   | 9.6/2.5 | H4 (2m)            | 1     | 19.2"    | 488 | 57.3                     | 26  | 0.46         | 0.69 |
| 1t                           | 2200       | ELK50-2ND100      | 16/4   | 5/1.3   | H4 (2m)            | 2     | 20.8"    | 528 | 61.7                     | 28  | 0.46         | 0.69 |
| 1/2T                         | 1100       | ELK100-1HD50*     | 63/16  | 19.5/5  | H4 (2m)            | 1     | 24.2"    | 617 | 136.6                    | 62  | 0.92         | 1.37 |
| 1T                           | 2200       | ELK100-1ND100*    | 32/8   | 9.6/2.5 | H4 (2m)            | 1     | 24.2"    | 617 | 136.6                    | 62  | 0.92         | 1.37 |
| 2T                           | 4400       | ELK100-2ND200*    | 16/4   | 5/1.3   | H4 (2m)            | 2     | 26.6"    | 676 | 145.5                    | 66  | 0.92         | 1.37 |
| 2T                           | 4400       | ELK200-1ND200     | 32/8   | 9.6/2.4 | H4 (1m)            | 1     | 27.1"    | 688 | 205.0                    | 93  | 1.49         | 2.22 |
| 3T                           | 6600       | ELK200-2ND300     | 16/4   | 4.8/1.2 | H4 (2m)            | 2     | 29.8"    | 756 | 224.0                    | 102 | 1.49         | 2.22 |
| 5T                           | 11000      | ELK250-2ND500     | 16/4   | 4.8/1.2 | H4 (2m)            | 2     | 34.4"    | 874 | 257.0                    | 117 | 2.37         | 3.53 |
|                              |            |                   |        |         |                    |       |          |     |                          |     |              |      |

